

CS1214

Subwoofer

JBL



Highlights

- 1000W peak power handling
- JBL® quality for car audio enthusiasts; performance and reliability at entry-level prices
- Works in sealed, vented and band-pass boxes and infinite-baffle applications

Key Specifications

	CS1214
Impedance:	4 Ohms
Frequency Response:	35Hz – 200Hz
Power Handling, RMS:	250W
Power Handling, Peak:	1000W
Voice-Coil Diameter:	50mm
Voice-Coil Excursion (X_{max})	21mm
Mounting Depth:	153mm
Cutout Diameter:	279mm
Overall Diameter:	311mm

CS1214

Subwoofer



FEATURES

Single 4-ohm voice coil

- Allows easy connectivity with both bridged full-range and mono subwoofer amplifiers

Improved power and efficiency

- 21mm linear one-way X_{max} and dual 1100g magnets for an impressive 1000W peak power handling

Polypropylene woofer cone

- Maximum woofer efficiency thanks to this lightweight cone material

Progressive spider

- Provides better control at excursion limits than a linear spider, resulting in reduced distortion at high output levels

Harman Consumer Group, Inc.
8500 Balboa Blvd., Northridge, CA 91329
www.jbl.com

 Harman International

© 2009 Harman International Industries, Incorporated. All rights reserved. JBL is a trademark of Harman International Industries, Incorporated, registered in the United States and/or other countries.

Features, specifications and appearance are subject to change without notice.